

GUV302G

UpStream 4k Game Capture Card with Party Chat Mixer



- Supports 4k@60 HDR input and pass-through
- Real time Ultra HD 4k@30 Video Capture on Laptop or PC via USB 3.1 Type C
- Supports up to 1440p@144Hz and 1080p@240Hz pass-through
- Supports party chat recording for Game Consoles
- UVC based driver

Unlock Your 4K Streaming Potential

The UpStream™ Game Capture Adapter (GUV302G) evolves the next generation of streaming with 4K @30Hz capture, passthrough resolutions designed for gamers including 4K @60Hz, 1440p @144Hz and 1080p @240Hz with built-in party chat mixer for any game console streamers.

4K @30Hz HDR Recording

Capture stunning 4K @30Hz quality for the latest 4K gameplay or stream and capture at 1440p @60Hz or 1080p @120Hz resolutions

Easy Plug & Play Design

No additional adapters or software to capture 4K gameplay or team chat via the latest game consoles

- | | |
|---|--|
| <ul style="list-style-type: none"> • Supports 4k@60 HDR input and pass-through • Real time Ultra HD 4k@30 Video Capture on Laptop or PC via USB 3.1 Type C • Supports up to 1440p@144Hz and 1080p@240Hz pass-through | <ul style="list-style-type: none"> • Supports party chat recording for Game Consoles • UVC based driver • Compatible with OBS software • Compliant with the Specification of High-Bandwidth Digital Content Protection (HDCP). |
|---|--|



Requirements

- Windows® 10, 11 w/ UVC support
- Mac OS X (10.2.x or later) w/ UVC support
- One available USB-A port, USB 3.1 is required for 4K Capture.
- Desktop: Intel® Core™ i5 6xxx above + NVIDIA GeForce GTX 1060 and above
Laptop: Intel® Core™ i7-7700HQ above + NVIDIA GeForce GTX 1050 Ti and above
- RAM: 8GB or higher

Package Contents

- 1 x GUV302G
- 1 x USB-C to A cable
- 1 x HDMI cable
- 1 x 3.5mm Audio cable
- 1 x Quick Start Guide

Specifications

| Function | GUV302G | Dimensions | GUV302G |
|--|--|--------------------------------|------------------------|
| Connectors | | Unit Dimensions | |
| USB | 1x USB-C for Host computer | Height | 0.66 " (1.7 cm) |
| Video Input | 3840x2160p 60/50/30/25/24Hz 2560x1440p 144/60/50/30/25/24Hz 1920x1080p 240/144/120/60/50/30/25/24Hz 1280x720p 60/50Hz 720x576p 50Hz 640x480 60Hz | Length | 1.7 " (4.4 cm) |
| Video Output | 1280x720p 60/50Hz 720x576p 50Hz 640x480 60 Hz | Width | 0.9" (2.5 cm) |
| Power | Bus Powered via USB-C to A cable | Inner Pack | |
| Video connections | | Height | *15.7 in (40 cm) |
| Input | 1x HDMI input up to 4K@60 HDR | Length | *7.4 in (19 cm) |
| Output | 1x HDMI input up to 4K@60 HDR | Width | *7 in (18 cm) |
| Video capture size | | Inner Pack Qty. | 6 pcs |
| UVC Capture: 3840x2160p 30/25Hz 2560x1440p 60/50/30/25Hz 1920x1080p 120/60/50/30/25Hz 1280x720p 60/50/30/25Hz 720x576p 50/25Hz 640x480p 60/30Hz | | Unit Package Dimensions | |
| Operating System Requirements | | Height | 7.4 in (19 cm) |
| Mac | Mac OS X (10.2.x or later) w/ UVC support | Length | 6.2 in (15.9 cm) |
| Windows | Windows® 10, 11 w/ UVC support | Width | 2.1 in (5.5 cm) |
| Operating System Support | | Master Carton | |
| One available USB-A port, USB 3.1 is required for 4K Capture. Desktop: Intel® Core? i5 6xxx above + NVIDIA GeForce GTX 1060 and above Laptop: Intel® Core? i7-7700HQ above + NVIDIA GeForce GTX 1050 Ti and above RAM: 8GB or higher | | Height | *16.5 in (42 cm) |
| Console Connectors | | Length | *15.9 in (40.5 cm) |
| Audio | 1x 3.5 mm for Headset 1x 3.5 mm for Console Gamepad | Width | *15.9 in (40.5 cm) |
| Cable Length | | Master Carton Qty. | 12 pcs |
| USB-C to A 3.3ft (1m) | | Weight | |
| | | Master Carton Wt. | *26.12 lbs (11.85 kgs) |
| | | Inner Pack Wt. | *2.68 lbs (1.21 kgs) |
| | | Unit Pack Wt. | *0.83 lbs (0.38 kgs) |
| | | Unit Wt. | 0.2 lbs (0.08 kgs) |