

GVS164W6

## 4-Port DVI Video Splitter with Audio



Simultaneously broadcast video across 4 displays. The video splitter is an ideal solution for simultaneous broadcasting environments and digital signage applications.

- Classrooms, exhibits, trade shows, monitor testing, demonstrations and multi-media presentations.
- Broadcasting video information such as news headlines, stock prices, airline flights and train schedules.
- Universities with multiple campuses, a single teacher to teach class to students in two or more locations at the same time

logear's DVI splitter supports both Analog & Digital video signal PLUS Audio.

- Connects computers with DVI graphics to multiple DVI compatible monitors or projectors
- Fully compliant with DVI-Digital and DVI-Analog
- Supports DDWG (Digital Display Working Group) standard for DVI compliant monitors
- Speaker enabled for audio enjoyment
- Cascadable to 3 levels
- Installs in minutes
- Maintains highest single link video resolution (1920 x 1200)
- DDC, DDC2, DDC2B Compatible (Port 1 only)



## Requirements

- Monitors and TVs with DVI connections
- Computers or source devices with DVI connections

## OS

- Windows XP, Windows Vista, Windows 7 32-/64-bit , Windows 8 32-/64-bit

## Package Contents

- 1 x IOGEAR 4 Port DVI Video Splitter
- 1 x DVI-D 6ft Cable
- 1 x Mini-Stereo Jack (Male) to Stereo RCA Jack (Male)
- 1 x Mini-Stereo Jack (Male) to Stereo RCA Jack (Female)
- 1 x Full Range Universal Power Adapter
- 1 x US to German Prong Adapter
- 1 x Quick Start Guide
- 1 x Warranty/ Registration Card

## Specifications

Function	GVS164W6	Dimensions	GVS164W6
<b>Housing</b>		<b>Unit Dimensions</b>	
Case	Metal	Height	1.75 in
<b>LEDs</b>		Depth	8.3 in
Power On	1	Width	3.2 in
<b>Power Consumption</b>		<b>Unit Package Dimensions</b>	
Video Resolution	1920 x 1200	Height	12 in
Operating Temperature	32F~122F (0C~50C)	Width	10 in
Storage Temperature	-4F~140F (-20C~60C)	Depth	3.25 in
<b>Operating System Support</b>		<b>Master Carton</b>	
Computers with Digital/ Analog DVI Display Support		Height	13.6in (34.50cm)
<b>Humidity</b>		Width	20.63 in (52.40cm)
0 - 80% RH (Non Condensing)		Depth	10.8 in (27.50cm)
<b>Daisy Chain</b>		Master Carton Qty.	6
Dependent on Signal Strength		<b>Weight</b>	
<b>Signal Type</b>		Master Carton Wt.	22 lb (10.00KG)
DVI-Digital and DVI-Analog		Unit Pack Wt.	3.3 lb (1.5KG)
<b>Cable Distance</b>		Unit Wt.	1.8 lbs
15 ft (4.6m)			
<b>Connectors (Input)</b>			
1 x DVI Female, 1 x Earphone Jack Female			
<b>Connectors (Output)</b>			
4 x DVI Female, 4 x Earphone Jack Female			