

GW4K30GH60KIT

Ultra-Fast 60GHz Wireless 4K HDMI® UHD Transmitter & Receiver Kit for 2 TVs



- Wirelessly send 4K UHD video from one HDMI source to 2 HDMI TV/Projectors
- Extends signals up to 40 Ft. line-of-sight
- Uncompressed audio and video at near-zero latency - ideal for gaming and streaming
- Resolutions up to 3840 x 2160 @30Hz
- Minimal interference with existing Wi-Fi devices via 60GHz wireless frequency

Eliminate Cables Without Sacrificing 4K HD Quality

With support for full UHD resolutions up to 4K @30Hz, the Ultra-Fast 60GHz Wireless 4K UHD Transmitter & Receiver Kit for 2 TVs can offer flexibility to place your 4K HDTV or HDMI projector anywhere up to 40 ft. or 12 meters in-room wirelessly from the HDMI capable video source without sacrificing picture and sound quality.

With near-zero latency, exceptional video resolutions of 3840 x 2160 and support for the newest 4K UHD High Dynamic Range TVs and content, the Ultra-Fast Wireless Transmitter and Receiver Kit enable both video and audio to be broadcast without any delay in real time. Save the time and expense of hiring installers to run messy HDMI cables through ceilings and walls.

- Wirelessly send 4K UHD video from one HDMI source to 2 HDMI TV/Projectors
- Extends signals up to 40 Ft. line-of-sight
- Uncompressed audio and video at near-zero latency - ideal for gaming and streaming
- Resolutions up to 3840 x 2160 @30Hz
- Minimal interference with existing Wi-Fi devices via 60GHz wireless frequency
- Support Master audio format



Specifications

Function	GW4K30GH60KIT	Dimensions	GW4K30GH60KIT
Video connections		Unit Dimensions	
Input	HDCP 2.2 Support	Height	3"
Output	HDCP 2.2 Support	Length	1.125"
Video Resolution	4K @30Hz	Depth	4"
Video Streaming	Uncompressed	Unit Package Dimensions	
Audio		Height	3.25"
Audio Output	LPCM Stereo	Length	9.50"
Frequency Band	60 GHz	Depth	7"
Antenna Type	Printed Circuit Board	Master Carton	
Environment		Height	10.25"
Operation Temperature	32~122°F (0~50°C)	Width	14.50"
Storage Temperature	14~158°F (-10~70°C)	Depth	10.25"
Humidity	10 - 90%	Master Carton Qty.	6
Power Adapter	Input: 100~240 VAC/0.3A, Output: 5VDC/2A	Weight	
Housing		Master Carton Wt.	22.30 lb
Case	Aluminum	Unit Pack Wt.	3.60 lb
Warranty	1-Year	Unit Wt.	rx 0.55 lb (x2) tx 1.25 lb
Power Consumption	TX 12W, RX 3W		