

#### GW4K30KIT

# Wireless 4K @ 30Hz Video Extender with Local Passthrough

- · Place your 4K TV nearly anywhere without the restrictions of HDMI cable lengths
- Stream wireless 4K audio & video up to 150 feet\* to a bedroom or patio
- · Setup two 4K TVs to share your 4K video content in a second location at the same time:
  - · Connect the first TV to the transmitter's HDMI Output port with an HDMI cable
  - · Receive content wirelessly from the same video source on the second TV



## Stream Wireless Audio and Stunning 4K Video up to 150 Feet

Create a completely customized setup in minutes, and transmit your favorite movies, sports, and videos within your home. IOGEAR's Wireless 4K Video Extender takes wireless home entertainment set-ups to the next level of connectivity with flexibility and convenience. Capable of streaming 4K content along with stereo audio up to 150 feet\* away with less than 200 Milliseconds of latency.

- Place your 4K TV nearly anywhere without the restrictions of HDMI cable lengths
- · Stream wireless 4K audio & video up to 150 feet\* to a bedroom or patio
- Setup two 4K TVs to share your 4K video content in a second location at the same time:
  - · Connect the first TV to the transmitter's HDMI Output port with an HDMI cable
  - · Receive content wirelessly from the same video source on the
- box or other video sources
- Enjoy stunning wireless 4K Ultra HD video resolutions (3840 x 2160)

- IR remote control extender allows video source control from second TV
- · Keep home theater electronic devices neatly out-of-sight
- No software or driver installation needed
- · No Wi-Fi network required
- HDMI 1.4 and HDCP 2.2 compliant
- H.264 Video compression with low latency (< 200ms)
- · Plug-N-Play solution


\*Distances may vary depending on environment. Solid and non-porous materials such as steel, concrete, brick and glass (varies depending on Transmit wireless video content from your Blu-ray player, DVR/cable coating and thickness) may cause shorter viewing distances or loss of signal. Line of sight is recommended for optimal performance.











#### Requirements

- Display
- 4K TV, 4K HD
   Display or 4K HD

   Projector with HDMI Input
- •
- Media Source
- 1 HDMI Output

#### **Package Contents**

- 1 x Wireless Transmitter
- 1 x Wireless Receiver
- 2 x HDMI Cables
- 2 x Power Adapters
- 1 x IR Extension Cable
- 1 x IR Blast Cable
- 1 x Quick Start Guide
- 1 x Warranty Card



### **Specifications**

Function				
Video Input         Transmitter: 1 x HDMI         Height         0.91 in           Video Output         Receiver: 1 x HDMI         Length         4.72 in           Power         1 x Power Jack (Tx and Rx)         Depth         3.15 in           Video Resolution         4800, 5769, 720p, 1080l, 1080p@ 60Hz, 2160p@ 80Hz,	Function	GW4K30KIT	Dimensions	GW4K30KIT
Video Output         Receiver: 1 x HDMI         Length         4.72 in           Power         1 x Power Jack (Tx and Rx)         Depth         3.15 in           Video Resolution         480p, 576p, 720p, 1080p, 1080p @ 60Hz, 2180p @ 30Hz         Unit Package Dimensions         4.33 in           Video Streaming         H.264 < 200ms Latency	Connectors		Unit Dimensions	
Power         1 x Power Jack (Tx and Rx)         Depth         3.15 in           Video Resolution         480p, 576p, 720p, 1080i, 1080p @ 60Hz, 2160p @ 30Hz         Unit Package Dimensions           Video Streaming         H.264 <200ms Latency         Height         4.33 in           Audio         Depth         6.93 in           Audio Output         PCM Stereo         Depth         6.93 in           Frequency         5 - 5.8 GHz         Master Carton         Height         9.84 in           Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         Weight         13.39 in           Infrared         Mester Carton Oty.         6         6           Frequency         20-60Hz Wide Range         Weight         12.35 ib           Case         Plastic         Unit Wt.         0.40 ib (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1-Year         4-158°F (-10-70°C)           Hunidity         10-90%         1-158°F (-10-70°C)           Hunidity         10-90%           Power Consumption         1-20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10.20 (10	Video Input	Transmitter: 1 x HDMI	Height	0.91 in
Video Resolution         480p. 576p. 720p. 1080j. 1080p @ 60Hz. 2160p @ 30Hz         Unit Package Dimensions           Video Streaming         H.264 < 200ms Latency	Video Output	Receiver: 1 x HDMI	Length	4.72 in
Video Streaming         H284 < 200ms Latency         Height         4.33 in           Audio         Width         9.45 in           Audio Output         PCM Stereo         Depth         6.93 in           Frequency         5 - 5.8 GHz         Master Carton         Height         9.84 in           Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (popth)         13.39 in           Infrared         Master Carton City.         6           Frequency         20.60Hz Wide Range         Weight         12.35 lb           Case         Plastic         Unit Pack Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Wortange         5 VDC         Voltage         5 VDC           Warranty         1-Year         4-158°F (-10-70°C)           Humidity         10.90%         4-158°F (-10-70°C)           Humidity         10.90%         4-158°F (-10-70°C)           BDIAD OUTPUT         HUMI 2.0, HDCP 2.2	Power	1 x Power Jack (Tx and Rx)	Depth	3.15 in
Video Streaming         H.284 < 200ms Latency         Width         9.45 in           Audio         Depth         6.93 in           Audio Output         PCM Stereo         Master Carton           Frequency         5 - 5.8 GHz         Height         9.84 in           Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         Depth         13.39 in           Infrared         Weight         4 Master Carton Qty;         6           Frequency         20-60Hz Wide Range         Weight         12.35 lb           Case         Plastic         Unit Pack Wit         1.55 lb           Case         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1-Year         Voltage         5 VDC           Warranty         1-Year         4-158% (-10-70°C)           Humidity         10-90%         4-158% (-10-70°C)           Humidity         10-90%         4-158% (-10-70°C)           Display Output	Video Resolution		-	
Audio Output         PCM Stereo         Depth         6.93 in           Frequency         5 - 5.8 GHz         Master Carton           Antenna Type         High Gain External         Height         9.84 in           Operating Range         Maximum video transmission range is 150ft (50m)         Depth         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         Depth         13.39 in           Infrared         Master Carton Oty.         6           Frequency         20-60Hz Wilde Range         Meight           Case         Plastic         Unit Pack Wt.         1.235 lb           Case         Plastic         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         VOIT         VOIT (10m)	Video Streaming	H.264 <200ms Latency		
Audio Output         PCM Stereo           Frequency         5 - 5.8 GHz         Height         9.84 in           Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         Depth         13.39 in           Infrared         Master Carton Qty.         6           Frequency         20-60Hz Wide Range         Weight           Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Pack Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Wortange         5 VDC           Warranty         1-Year           Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (10-70°C)           Humidity         10-90%           Power Consumption         10-90%           Bipply Output           HDMI         HDMI 2.0, HDCP 2.2	Audio			
Frequency         5 - 5.8 GHz         Height         9.84 in           Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         bepth         13.39 in           Infrared         Master Carton Qty.         6           Frequency         20-60Hz Wide Range         Weight           Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Vex.         0.40 lb (x 2)           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1Year         Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)         + Very Consumption         + Very Consumption           Display Output         HDMI 2.0, HDCP 2.2         + DDMI 2.0, HDCP 2.2	Audio Output	PCM Stereo	•	6.93 in
Antenna Type         High Gain External         Width         14.25 in           Operating Range         Maximum video transmission range is 150ft (50m)         Depth         13.39 in           Infrared         Master Carton Qty.         6           Frequency         20-60Hz Wide Range         Weight           Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1-Year           Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)           Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI 2.0, HDCP 2.2	Frequency	5 ~5.8 GHz		
Operating Range         Maximum video transmission range is 150ft (50mm)         Depth         13.39 in           Infrared         Master Carton City.         6           Frequency         20-60Hz Wide Range         Weight           Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1Year         1-Year           Operating Temperature         14-158°F (-10-70°C)         4-158°F (-10-70°C)           Humidity         10-90%         Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI 2.0, HDCP 2.2	Antenna Type	High Gain External		
Infrared         Master Carton Qty.         6           Frequency         20-60Hz Wide Range         Weight           Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Pack Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1-Year         Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)         Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI 2.0, HDCP 2.2	Operating Range			
Frequency   20-60Hz Wide Range   Weight		(50m)		
Housing         Master Carton Wt.         12.35 lb           Case         Plastic         Unit Pack Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage         5 VDC           Warranty         1-Year         Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)         Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W         Display Output           HDMI         HDMI 2.0, HDCP 2.2			·	6
Case         Plastic         Unit Pack Wt.         1.55 lb           Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage           Voltage         5 VDC         Voltage         5 VDC           Warranty         1-Year         Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)         Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI 2.0, HDCP 2.2		20-60Hz Wide Range	_	
Power         Unit Wt.         0.40 lb (x 2)           Amps         Input 0.3A, Output 2A         Voltage           Voltage         5 VDC         Voltage         5 VDC           Warranty         1-Year         Voltage Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)         Voltage         Voltage           Humidity         10-90%         Voltage         Voltage         Voltage           Power Consumption         ransmitter: 7 W, Receiver: 5 W         Voltage         Voltage         Voltage           Display Output         HDMI         HDMI 2.0, HDCP 2.2         Voltage         Voltage </td <td>-</td> <td></td> <td></td> <td></td>	-			
Amps         Input 0.3A, Output 2A           Voltage         5 VDC           Warranty         1-Year           Operating Temperature         32–122°F (0–50°C)           Storage Temperature         14–158°F (-10–70°C)           Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI 2.0, HDCP 2.2	Case	Plastic	Unit Pack Wt.	1.55 lb
Voltage         5 VDC           Warranty         1-Year           Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)           Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output           HDMI         HDMI 2.0, HDCP 2.2	Power		Unit Wt.	0.40 lb (x 2)
Warranty         1-Year           Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)           Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI           HDMI         HDMI 2.0, HDCP 2.2	Amps	Input 0.3A, Output 2A		
Operating Temperature         32-122°F (0-50°C)           Storage Temperature         14-158°F (-10-70°C)           Humidity         10-90%           Power Consumption         ransmitter: 7 W, Receiver: 5 W           Display Output         HDMI           HDMI         HDMI 2.0, HDCP 2.2	Voltage	5 VDC		
Storage Temperature 14~158°F (-10~70°C)  Humidity 10-90%  Power Consumption ransmitter: 7 W, Receiver: 5 W  Display Output  HDMI HDMI 2.0, HDCP 2.2	Warranty	1-Year		
Humidity 10-90%  Power Consumption ransmitter: 7 W, Receiver: 5 W  Display Output  HDMI HDMI 2.0, HDCP 2.2	Operating Temperature	32~122°F (0~50°C)		
Power Consumption ransmitter: 7 W, Receiver: 5 W  Display Output  HDMI HDMI 2.0, HDCP 2.2	Storage Temperature	14~158°F (-10~70°C)		
Display Output  HDMI HDMI 2.0, HDCP 2.2	Humidity	10-90%		
HDMI HDMI 2.0, HDCP 2.2	Power Consumption	ransmitter: 7 W, Receiver: 5 W		
72 - 1	Display Output			
Transfer Rate Max 10.2 Ghos	НОМІ	HDMI 2.0, HDCP 2.2		
THE TOTAL CORPO	Transfer Rate	Max 10.2 Gbps		