

GWA501

Wireless-G Broadband Gateway



- Easy Fast and simple setup via wizard
- Complete Includes everything you need for effortless installation and configuration
- Secure Built-in Firewall, supports WPA and WEP



- Versatile Backward compatible with 802.11b devices
- Accessible Share DSL/Cable connection
- Practical Built-in print server



Requirements

PC system

- 200MHz or faster CPU
- Internet browser
- Microsoft Windows 98/ME/2000/XP
- Ethernet interface card or WLAN client card installed

Package Contents

- Wireless-G Broadband Gateway
- Manual CD
- Quick Start Guide
- Warranty Card
- Power Adapter
- Ethernet Cable

Mac system

- G3 Power Mac or higher
- Mac OS 9.2 and above
- Open Ethernet port or Airport card installed

Specifications

Function	GWA501	Dimensions	GWA501
LEDs		Unit Dimensions	
Power On	1	Height	1.38 in. (3.4 cm.)
WAN	1	Length	7.25 in. (18.5 cm,)
WLAN	1	Width	5.25 in. (13.3 cm.)
LAN	4	Unit Package Dimensions	
Operating Temperature	0 ~ 50°C	Height	10.125 in.
Storage Temperature	-20~65°C	Width	8.875 in.
Operating System Support	Windows 98SE/ME/2000/NT 4.0/XP, Mac OS 9.2 and above	Depth	3.875 in.
Transfer Rate	54,48,36,24,18,12,11,6,5.5,2,1Mbps, auto- fallback	Master Carton	
		Height	11.5 in. (29.21 cm.)
Humidity	10% - 90% non-condensing	Width	18.25 in. (46.35 cm.)
Network Protocol	TCP/IP	Depth	20.25 in. (51.44 cm.)
Frequency Band	2.400 ~ 2.4835 GHz	Master Carton Qty.	10
Modulation	CCK, BPSK, QPSK, 16-QAM, 64-QAM	Weight	
Sensitivity	-85 dBm(typical)	Master Carton Wt.	33 lbs. (15 Kg.)
Security	Support WEP (64,128bit), WPA	Unit Pack Wt.	2.96 lbs.
Printer Connection	USB	Unit Wt.	0.71 lbs. (0.32 kg.)
Standards	IEEE 802.11g and 802.11b		
Management	Web-based management		
Operating Range	Open Space: 11Mbps up to 300m, 54Mbps up to 50m		
Number of Channel	11		
RF Spreading	OFDM, DSSS		
Antenna Type	Two Dipole Diversity Antenna		