

GWH DSTX

Wireless Video Transmitter



Wireless Video

IOGEAR's Wireless Video Transmitter (GWH DSTXB) is the perfect companion for the [Wireless 5x2 HD Matrix's receiver \(GWH DMS52\)](#) and the [Wireless Video Transmitter and Receiver Kit \(GWH D11\)](#); sending uncompressed Full HD 1080p from your laptop, computer, game console and or other HDMI device. It adds an additional HDMI device to your existing Wireless 5x2 HD Matrix set up. Add up to a total of 3 Wireless Video Transmitters to one (1) GWH DMS52 set up.

The simplified Wireless Transmitter does not require any drivers or software, just plug it into the HDMI port of your HDMI device and you are sending wireless audio/video up to 30ft from the Wireless 5x2 HD Matrix receiver.

Wireless PC to TV

Take advantage of your large screen HDTV and send your computer's screen wirelessly for all your internet browsing, favorite video sites, shopping, reviewing and sharing of your photos and videos.

Wireless Gaming

With less than 1ms latency you can set your computer or game console up for wireless gaming! The Wireless Video Transmitter does not require a line-of-sight placement enabling a quick, simple, and flexible wireless audio/video solution.



How does it work?

- Connect GWHDSTX to a laptop or media player HDMI port
- Pair with IOGEAR's Wireless 5x2 HD Matrix (GWHDMS52) receiver that is connected to an HDTV
- Wirelessly play content on your HDTV



*Receiver Model: GWHDMS52

Requirements

Hardware:

- Wireless 5x2 HD Matrix (Part# [GWHDMS52](#)) or the Wireless HDMI Transmitter and Receiver Kit (Part# [GWHD11](#))

Display:

- HDTV

Media Source:

- HDMI Output

Package Contents

- 1 x Wireless HDMI Transmitter
- 1 x Mini USB to USB Cable
- 1 x Mini USB Power Adapter
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GWHDSTX	Dimensions	GWHDSTX
Connectors		Unit Dimensions	
Power	1 x Mini USB Power Jack	Height	0.66" (1.68 cm)
Video Input	1 x HDMI Connection (Type A, male)	Depth	1.19" (3.02 cm)
Video Resolution	up to 1080p (50 / 60Hz) and 3D support	Length	3.25" (8.26 cm)
Video Streaming	<1ms Latency	Unit Package Dimensions	
Audio		Width	4.25" (10.8 cm)
Audio Output	Digital 6Mbps, 2 to 8 channels 16~ 24 bits/s by I2S and S/P DIF bus over WHDI transmission (Dolby Digital & DTS)	Height	3.63" (9.22 cm)
Frequency	4.9 ~ 5.9 GHz (Includes Non-DFS and DFS Frequency Bands)	Depth	2.93" (7.44 cm)
Antenna Type	High Performance Internal	Master Carton	
Range	Maximum video transmission range is 30ft (10m)	Width	16.02" (40.69 cm)
Power Switch	1 x Button	Height	13.88" (35.3 cm)
Power		Depth	7.38" (18.7 cm)
Voltage	5V DC Mini USB	Master Carton Qty.	24
Amps	1.5A	Weight	
Housing		Master Carton Wt.	14.05lbs (6.37kg)
Case	Plastic	Unit Pack Wt.	0.50lbs (0.23 kg)
Cable Connections		Unit Wt.	0.05lbs (0.023kg)
Input	1 x Mini USB (female)		
LEDs			
Port Status	1 x Blue LED		