

GWLR4K60KIT

Ultra Long-Range Wireless 4K @ 60Hz Video Transmitter and Receiver Kit



- Quickly add or change TV/display locations as needed
- Wirelessly send 4K Ultra HD video up to 600 ft.
- Supports 4K UHD resolutions of up to 3840 x 2160 @ 60Hz refresh rates
- Perfect for large homes, retail, medical lobbies, and small commercial applications
- Transmit from an HDMI®-enabled source to up to 3 TVs with additional receivers (GWLR4K60RX)

Flexible TV or Display Placement


Enjoy crystal-clear quality from an HDMI 2.0 source and the newest 4K Ultra High Definition (UHD) High Dynamic Range TVs and content with resolutions reaching 3840 x 2160 at a 60Hz refresh rate. By eliminating the bulk of HDMI wiring over long distances, the Wireless 4K Video transmitter and receiver affords greater flexibility in TV/display placement. Quickly place TVs in temporary environments such as on a patio or in the kitchen and add a second or third TV with additional wireless receivers.

Control Source Device Remotely With IR Support

Easily control your source remotely from the TV with the included IR blast and extension cables. Once the IR cables are connected, point your remote control at the Wireless 4K Video receiver and press a button to control the source. This feature only works from the system's HDMI receiver (GWLR4K60RX).

- Quickly add or change TV/display locations as needed
- Wirelessly send 4K Ultra HD video up to 600 ft.
- Supports 4K UHD resolutions of up to 3840 x 2160 @ 60Hz refresh rates
- Perfect for large homes, retail, medical lobbies, and small commercial applications
- Transmit from an HDMI®-enabled source to up to 3 TVs with additional receivers (GWLR4K60RX)
- Control sources & extend the IR remote range using the included IR blasters
- Secure 5 GHz Wi-Fi WPA-2 personal security encryption
- HDMI 2.0 and HDCP 2.2 Compliant
- H.264 Video compression
- Plug-N-Play solution - No existing wireless network needed





Requirements

- **Display**
- Display or Projector with HDMI Input
- **Media Source**
- 1 HDMI Output

Package Contents

- 1 x Ultra Long Range Wireless Transmitter with HDMI
- 1 x Ultra Long Range Wireless Receiver with HDMI
- 2 x HDMI Cables
- 2 x Power Adapter
- 2 x IR Blast Cables
- 1 x Quick Start Guide
- 1 x Warranty Card

Specifications

Function	GWLR4K60KIT	Dimensions	GWLR4K60KIT
Connectors		Unit Dimensions	
Video Output	HDCP 2.2 Support	Height	1.75 in
Power	1 x Power Jack	Length	7.63 in
Video Resolution		Depth	4.50 in
3840 x 2160 @ 60Hz; 1920x1080@60Hz; 1680x1050@60Hz; 1440x900@60Hz; 1360x768@60Hz; 1280x1024@60Hz; 1280x960@60Hz; 1280x720@60Hz; 1024x768@60Hz; 800x600@60Hz		Unit Package Dimensions	
Video Streaming		Height	6.00 in
<200ms Latency H.264		Length	14.75 in
Audio		Depth	3.35 in
Audio Output	L/R Stereo Audio	Master Carton	
Codec	PCM	Height	11.25 in
Frequency	5.1 ~ 5.8 G Wireless Transmission	Width	15.50 in
Antenna Type	Dual Hi-Gain 5 DBi	Depth	13 in
Operating Range	Up to 600 Feet	Master Carton Qty.	6
Infrared		Weight	
Frequency	IR Passback 20-60 KHz	Master Carton Wt.	31.31 lb (14.2 KGs)
Housing		Unit Pack Wt.	4.85 lb (2.2 KGs)
Case	Iron alloy and crystal panel	Unit Wt.	1.45 lb (0.66 KGs)
Power			
Amps	3.1 A		
Voltage	5 VDC		
Warranty	1-Year		
Operating Temperature	32~122°F (0~50°C)		
Power Consumption	TX <11W / RX <12W		
Environment			
Humidity	0~90%		
Transfer Rate	18 Gbps		